SEGWAY Drift W1 - PBCDRIFTF1


























Silicone Bumpers
RGB LED Lights
45 Mins Battery Range
22-220 lbs (10-100 kg) Payload
10% Hill Grade
IPX6 Splash Proof
Portable

Rating: Not Rated Yet
Price

$699.00

Ask a question about this product

Description

Segway Drift W1

Dimensions	Mainframe (single wheel)	11.5×6.4×4.8 in (291×162×121 mm)
	Unit	12.5×10.6×8.7 in (318×269×219 mm)
Weight	Net (single wheel)	Approx. 7.7 lbs (3.5 kg)
Rider	Payload	22-220 lbs (10-100 kg)
	Recommended Age	6+ years old. See the weight limit
	Max. Speed	Approx. 7.5 mph (12 km/h) Top speed will vary based on riding style and remaining battery life. Top speed will be reduced when the battery is low.
	Typical Riding Time	45 minutes
	Max. Slope	10°
	Traversable Terrain	Flat, hard ground free of bumps or obstacles
Machine Parameters	Operating Temperature	14-104°F (-10-40°C)
	Storage Temperature	-4-122°F (-20-50°C)
	IP Rating	Mainframe IP54/ Battery pack IPX6
	Max. Storage Time	Approx. 180 days/100% power; Approx. 30 days/30% power
	Charge Time (for both mainframes)	Approx. 3 hours
	Nominal Voltage	22.2 VDC
	Max. Charging Voltage	25.2 VDC
	Charging Temperature	32-104°F (0-40°C)
Battery	Nominal Capacity	44.4 Wh

Segway Drift W1

	Battery Management System	Over-voltage, under-voltage, over-current, short circuit, and over-heating protection. Auto-sleep, auto-balance, and auto-wake.
Motors	Max. torque (single wheel)	6 Nm
	Output Power	37.5 W
	Input Voltage	100-240 VAC
Charger	Output Voltage	25 ± 0.2 VDC
	Output Current	1.5A